

# USAlert WatchDog™

USAlert's continuation of  
advanced paging products and  
service excellence....

The **WatchDog** is a very simple, loud, and rugged voice pager. It offers single channel, dual channel, or five channel operation.

True alphanumeric display allows source alert text messaging and message time stamping. Display menu also makes operational changes simple and fast (i.e. Selecting from three scan mode types, which frequencies to operate on, setting time and date, etc).

Choice of tone alert, vibrate alert, or simultaneous tone and vibrate. On/Off Duty capability. Option of up to four minutes of stored voice.

The Watchdog has an IP66 Rating. Total protection against dust and temporary flooding of water (i.e. ship deck).



A man's best friend is his dog .....  
a fireman's best friend is his **WatchDog™**

Assembled in the United States of America

**USAlert, LLC.**

1809 S. Powerline Rd., Suite 101  
Deerfield Beach, FL 33442

**561. 394. 9969**

**[www.usalertllc.com](http://www.usalertllc.com)**

Synthesized and Five Channel

## Features:

- Two Tone Decoding Format
- 15 Addresses Per Channel
- Optional 2 or 5 Channel
- Tone Alert, Vibrate Alert or Tone-Vibe alert
- On / Off Volume Control
- Alphanumeric Display
- Quick Monitor Control
- Audio Lock On
- Multi Function Scan
  - Channel Scan
  - Selective Call Scan
  - Priority Scan
- Low Battery Alert
- Wideband and Narrowband Models
- Programmable Text Alert Messaging
- Alert Time Stamping
- Optional 4 Minutes Voice Memory
- Forward Message Playback Select
- Reverse Message Playback Select
- Delete Message
- Delete all Messages
- Message Protect
- 3 Bar Graphic Battery Level Indication
- Menu selectable options
- AAA Rechargeable Batteries included
- Compatible w/ Alkaline Batteries as well

Band	VHF	UHF
Frequency Range MHz	138 - 174	406 - 512
Frequency Stability	+/- 0.0010%	+/- 0.0005%
Channel Spacing	12.5 KHz / 25 KHz	12.5 KHz / 25 KHz
Sensitivity / Alerting	2.0 uV/m	3.5 uV/m
Sensitivity / 12dB SINAD	4uV/m	10uV/m
Adjacent Channel Selectivity	65dB	65dB
Spurious & Image Rejection	>55dB	>55dB
Audio Output Linear	> 750 mw	> 750 mw
Alert	100dB SPL @ 12"	100dB SPL @ 12"
Voice	98dB SPL @ 12"	98dB SPL @ 12"
Audio Distortion	< 2%	< 2%
Battery Life Ni-MH	5 days	5 days
Battery Life Alkaline	7 days	7 days
Dimensions	4.5" X 2.25" X 1.0"	4.5" X 2.25" X 1.0"
Weight	205g	205g